Lever Hoist Powertex PLH-S2 with Corolim® Chain

Product information



The Powertex PLH-S2 Lever Hoist is a high-quality hoist designed for durability, safety, and ease of operation. Its ergonomic ratchet lever, and safety-added features ensure smooth and efficient lifting for various industrial applications.

Product benefits:

Enhanced safety: each hoist undergoes dynamic proof load testing at 1.5 times the Working Load Limit (WLL) before leaving the factory, ensuring maximum safety and reliability. The hoist is equipped with a well-covered automatic load reaction brake and features double safety with two brake pawls and four brake springs, exceeding EN 13157 requirements. The load chain is calibrated, proof load tested and meets the requirements of EN 818-7.

Smooth and efficient operation: the compact and lightweight construction, combined with a sprocket wheel equipped with needle bearings and a drive shaft supported by needle and slide bearings, ensures smooth and efficient operation. The fine-calibrated European-made COROLIM® protected load chain offers quiet and seamless performance.

Load chain with superior corrosion resistance: the unique COROLIM® surface treatment of the load chain provides excellent corrosion protection, equivalent to ISO944-9 C5High / ISO9223 C3 standards, ensuring long-lasting durability even in harsh environments.

Easy positioning and safe hooks: swivel hooks at both ends make in-line positioning easy. The hooks are designed to open at overload instead of breaking, enhancing safety. Heavy-duty steel safety latches and deformation check dots forged into the side of the hooks allow for easy overload detection.

Convenient maintenance and documentation: each hoist is RFID-equipped for easy service and inspection, and a QR code provides on-site access to multilingual user manuals. A test certificate and Declaration of Conformity are enclosed with each hoist, ensuring compliance and traceability.

... Read more

Material: Durable all steel construction
Marking: According to standard, CE-mark, Powertex, Model, WLL, Chain, Serial number, User manual/QR code
Temperature range: -10°C up to +50°C
Finish: Powder coated finish and plated frame components
Standard: EN 13157, EN 818-7

Safety factor: 4:1

© November 2026 - All Rights Reserved

Lever Hoist Powertex PLH-S2 with Corolim® Chain

Blueprint



Technical data

Part code	WLL ton	Lifting height m	Number of falls	Weight kg	Model	Load chain mm	Hand force max. kg	A mm	B mm	C mm	D mm	E mm	F mm	H min mm
500500030150560	0.25	1.5	1	2.7	PLH-S2/250KG PHC	4,0 x 12,0	28.2	100	70	86	163	20	31	235
500500030300560	0.25	3	1	3.23	PLH-S2/250KG PHC	4,0 x 12,0	28.2	100	70	86	163	20	31	235
500500050150560	0.5	1.5	1	5.2	PLH-S2/500KG PHC	5,0 x 15,0	24.8	150	90	118	253	22	32	310
500500050300560	0.5	3	1	5.2	PLH-S2/500KG PHC	5,0 x 15,0	24.8	150	90	118	253	22	32	310
500500080150560	0.8	1.5	1	6.6	PLH-S2/800KG PHC	5,6 x 17,0	26.5	158	98	132	273	26	36	340
500500080300560	0.8	3	1	7.6	PLH-S2/800KG PHC	5,6 x 17,0	26.5	158	98	132	273	26	36	340
500500160150560	1.6	1.5	1	11	PLH-S2/1600KG PHC	7,1 x 21,0	29.5	185	111	145	378	29	43	400
500500160300560	1.6	3	1	12.6	PLH-S2/1600KG PHC	7,1 x 21,0	29.5	185	111	145	378	29	43	400
500500320150560	3.2	1.5	1	19.9	PLH-S2/3200KG PHC	10,0 x 28,0	33.5	212	124	198	418	37	50	520
500500320300560	3.2	3	1	23.2	PLH-S2/3200KG PHC	10,0 x 28,0	33.5	212	124	198	418	37	50	520
500500630150560	6.3	1.5	2	24.6	PLH-S2/6300KG PHC	10,0 x 28,0	37	212	124	230	418	43	53	640
500500630300560	6.3	3	2	31.2	PLH-S2/6300KG PHC	10,0 x 28,0	37	212	124	230	418	43	53	640
500500900150560	9	1.5	3	50	PLH-S2/9000KG PHC	10,0 x 28,0	42	212	124	338	418	44	67	730
500500900300560	9	3	3	60	PLH-S2/9000KG PHC	10,0 x 28,0	42	212	124	338	418	44	67	730

© November 2026 - All Rights Reserved