Push Trolley Powertex PPT-S2

Product information



Powertex PPT-S2 is a high quality, durable low built push trolley that is easy to install on horizontal beams and rails.

The trolleys can be used for I-beams with plane flanges (such as IPE, HEA or HEB types) or beams with sloping flanges (such as INP-beams).

The trolley can easily be positioned along the beam by pushing or pulling thanks to high quality steel wheels with bearings.

Features:

- Safe - All Powertex trolleys are proof load tested 1,5 x WLL
- **Mechanical stops integrated in the design** to prevent derailing
- Equipped with connection plate with eye to hoist's upper hook or direct connection
- Connection plate can be turned 90 degrees to allow direct connection to Powertex S2 hoists without need of intermediate hook/eye
- Rubber bumpers to absorb shock loads on impact to rail ending
- Equipped with RFID for quick registration and maintenance
- Marked with QR code to allow access to user manuals at any time
- PPT-S2 is easy to mount and dismount on a horizontal rail or beam
- The 3 piece design makes installation quick and ergonomically
- The shaft is easily locked using the lock plate (No need to use large castle nut nor collar pins)
- Wheel shafts are robotic welded for high quality weld seams
- Large steel wheels equipped with double sided sealed bearings tha... *Read more*


Marking: According to standard, CE-mark, WLL, beam width, individual serial number
Temperature range: -10°C up to +50°C.
Finish: Black powder painted (Matt finish)
Standard: EN 13157, AS 1418.2

Safety factor: 4:1

© November 2026 - All Rights Reserved

Push Trolley Powertex PPT-S2

Blueprint



Technical data

Part code	WLL ton	Beam width mm	Weight kg	Model	Minimum radius mm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	J mm	S mm
502500031520210	0.25	50-152	4.6	PPT-S2	800	188	208	137	50	29	1 – 1,5	28	6	104	27
502500051350210	0.5	50-135	6.8	PPT-S2	800	205	198	150	55	30	1,5 – 2	28	8	111	27
502500052150210	0.5	130-215	7.6	PPT-S2	800	205	278	150	55	30	1,5 - 2	28	8	111	27
502500053000210	0.5	215-300	8.4	PPT-S2	800	205	363	150	55	30	1,5 – 2	28	8	111	27
502500101400210	1	55-140	11.2	PPT-S2	1,000	242	211	174	68	30	1,5 – 2	32	10	118	28
502500102150210	1	140-215	12.2	PPT-S2	1,000	242	286	174	68	30	1,5 – 2	32	10	118	28
502500103000210	1	215-300	13.5	PPT-S2	1,000	242	371	174	68	30	1,5 – 2	32	10	118	28
502500201550210	2	65-155	16.9	PPT-S2	1,100	270	238	194	80	49	1,5 – 2	40	12	147	27
502500202300210	2	150-230	18.1	PPT-S2	1,100	270	313	194	80	49	1,5 – 2	40	12	147	27
502500203000210	2	230-300	19.3	PPT-S2	1,100	270	383	194	80	49	1,5 – 2	40	12	147	27
502500301600210	3	90-160	28.6	PPT-S2	1,300	325	246	234	100	60	2 – 3	49	14	177	29
502500302300210	3	160-230	30.2	PPT-S2	1,300	325	316	234	100	60	2 – 3	49	14	177	29
502500303000210	3	230-300	31.8	PPT-S2	1,300	325	386	234	100	60	2 – 3	49	14	177	29
502500501800210	5	90-180	44.8	PPT-S2	1,500	370	280	267	110	79	2 – 3	59	16	219	29
502500502300210	5	180-230	46.5	PPT-S2	1,500	370	330	267	110	79	2 – 3	59	16	219	29
502500503000210	5	230-300	48.9	PPT-S2	1,500	370	330	267	110	79	2 – 3	59	16	219	29

© November 2026 - All Rights Reserved