

## Lashing Chain Powertex PLC

### Product information



### **POWERTEX**

Powertex Lashing chains PLC are made of high strength Grade 8 round steel chains and latch hooks at each end.

The chains are designed to allow quick and safe hooking to the trailer and/or to the load to be secured.

- Safe – Powertex Lashing chains are strong and reliable and consist of EN standard compliant chains and hooks
- Lashing chains are made to EN 12195-3
- Black electrophoretic painted chains Grade 8 acc to EN 818-2
- Red powder painted clevis hooks with heavy duty latches acc to EN 1677-2
- Each lashing chain assembly is marked with a durable Aluminum Identification tag
- Intended to be used with Powertex load binder
- Multilanguage user manuals included

**Material:** High strength chain and hooks in Grade 8 acc to EN standard

**Marking:** According to standard, Powertex, Lashing capacity, "Lashing chain - Not for lifting"!, Manufacturing date, Batch number. For 2-part lashing the STF is marked on the tensioner, not on the chain!

**Temperature range:** -40°C up to + 200°C.

**Finish:** Black electrophoretic painted chains and red powder painted hooks

**Standard:** EN 12195-3, EN 818-2, EN 1677-2

**Note:** For 2-part lashing the STF is marked on the tensioner, not on the chain

**Warning:** Not approved for lifting.

| Part code       | Chain diameter<br>mm | LC<br>kN | LC<br>daN | MBL<br>ton | EWL<br>m | Type  | Weight<br>kg |
|-----------------|----------------------|----------|-----------|------------|----------|-------|--------------|
| 704100800500090 | 8                    | 40       | 4,000     | 8          | 5        | PLC8  | 7.8          |
| 704100800800090 | 8                    | 40       | 4,000     | 8          | 8        | PLC8  | 12.7         |
| 704100801000090 | 8                    | 40       | 4,000     | 8          | 10       | -     | 15.7         |
| 704101000350090 | 10                   | 63       | 6,300     | 12.6       | 3.5      | PLC10 | 9.3          |
| 704101000500090 | 10                   | 63       | 6,300     | 12.6       | 5        | PLC10 | 12.6         |
| 704101000600090 | 10                   | 63       | 6,300     | 12.6       | 6        | PLC10 | 15.3         |
| 704101000800090 | 10                   | 63       | 6,300     | 12.6       | 8        | PLC10 | 19.7         |
| 704101001000090 | 10                   | 63       | 6,300     | 12.6       | 10       | PLC10 | 23.9         |
| 704101300500090 | 13                   | 100      | 10,000    | 21.2       | 5        | PLC13 | 21.6         |
| 704101300800090 | 13                   | 100      | 10,000    | 21.2       | 8        | PLC13 | 32.8         |
| 704101301000090 | 13                   | 100      | 10,000    | 21.2       | 10       | PLC13 | 40.6         |
| 704101600500090 | 16                   | 160      | 16,000    | 32         | 5        | PLC16 | 33.9         |
| 704101600600090 | 16                   | 160      | 16,000    | 32         | 6        | PLC16 | 39.7         |
| 704101600800090 | 16                   | 160      | 16,000    | 32         | 8        | PLC16 | 51.3         |