



## Chain Block Powertex PCB-S2OLP with Corolim® Chain

### Product information

#### **POWERTEX**

The Powertex PCB-S2 OLP Chain Hoist is a high-quality chain block designed to provide durability, safety, and ease of operation. With its ergonomic hand chain, advanced features, and built-in overload protection, this chain hoist ensures smooth and efficient lifting for various industrial applications. This OLP version has an integrated Overload Protection, which ensures safe lifting and prevents unintended overloading of the hoist.

#### **Product benefits:**

**Overload protection device:** the OLP hoists are factory-equipped with an Overload Protection device, which limits the maximum operating force that can be applied using the hand chain, ensuring safe and controlled lifting operations.

**Enhanced safety:** each hoist undergoes dynamic proof load testing at 1.5 times the Working Load Limit (WLL) before leaving the factory, ensuring maximum safety and reliability. The hoist is equipped with a well-covered automatic load reaction brake and features double safety with two brake pawls and four brake springs, exceeding EN 13157 requirements. The load chain is calibrated, proof load tested and meets the requirements of EN 818-7.

**Smooth and efficient operation:** the compact and lightweight construction, combined with a sprocket wheel equipped with needle bearings and a drive shaft supported by needle and slide bearings, ensures smooth and efficient operation. The fine-calibrated European-made COROLIM® protected load chain offers quiet and seamless performance.

**Load chain with superior corrosion resistance:** the unique COROLIM® surface treatment of the load chain provides excellent corrosion protection, equivalent to ISO944-9 C5High / ISO9223 C3 standards, ensuring long-lasting durability even in harsh environments.

**Easy positioning and safe hooks:** swivel hooks at both ends make in-line positioning easy. The hooks are designed to open at overload instead of breaking, enhancing safety. Heavy-duty steel safety latches and deformation check dots forged into the side of the hooks allow for easy overload detection.

**Convenient maintenance and documentation:** each hoist is RFID-equipped for easy service and inspection, and a QR code provides on-site access to multilingual user manuals. A test certificate and Declaration of Conformity are enclosed with each hoist, ensuring compliance and traceability.

**Available spare parts:** spare parts such as hooks, brake discs, safety latches, and chains are readily available, ensuring that maintenance and repairs can be carried out efficiently and further extending the hoist's service life.

**Product options:**

**Chain bag:** an optional chain bag is available for added convenience and organization.

**Material:** Durable all steel construction

**Marking:** According to standard, CE-marked, UKCA-marked, Powertex, Model, WLL, Chain, Serial number, User manual/QR code

**Temperature range:** -10°C up to +50°C

**Finish:** Red powder coated body and plated frame components

**Standard:** EN 13157, EN 818-7

**Safety factor:** 4:1

Part code	WLL ton	Lifting height m	Number of falls	Weight kg	Model	Load chain mm	Hand chain mm	Hand force max. kg	A, B, C, D, H min mm
500100050300181	0.5	3	1	9.8	PCB-S2OLP/500KG PHC	5,0 x 15,0	5,0 x 23,7	24.9	130 128 22 34 280
500100050600181	0.5	6	1	9.8	PCB-S2OLP/500KG PHC	5,0 x 15,0	5,0 x 23,7	24.9	130 128 22 34 280
500100100300181	1	3	1	11.7	PCB-S2OLP/1000KG PHC	6,3 x 19,0	5,0 x 23,7	28.4	150 145 26 39 330
500100100600181	1	6	1	12	PCB-S2OLP/1000KG PHC	6,3 x 19,0	5,0 x 23,7	28.4	150 145 26 39 330
500100200300181	2	3	1	18.9	PCB-S2OLP/2000KG PHC	8,0 x 24,0	5,0 x 23,7	34.3	185 175 35 49 385
500100200600181	2	6	1	19.5	PCB-S2OLP/2000KG PHC	8,0 x 24,0	5,0 x 23,7	34.3	185 175 35 49 385
500100300300181	3	3	2	28.9	PCB-S2OLP/3000KG PHC	7,1 x 21,0	5,0 x 23,7	34.3	220 158 37 50 510
500100300600181	3	6	2	28.9	PCB-S2OLP/3000KG PHC	7,1 x 21,0	5,0 x 23,7	34.3	220 158 37 50 510
500100500300181	5	3	2	37.1	PCB-S2OLP/5000KG PHC	9,0 x 27,0	5,0 x 23,7	37.2	255 183 43 60 615
500100500600181	5	6	2	51.05	PCB-S2OLP/5000KG PHC	9,0 x 27,0	5,0 x 23,7	37.2	255 183 43 60 615
500100750300181	7.5	3	3	50	PCB-S2OLP/7500KG PHC	9,0 x 27,0	5,0 x 23,7	36.8	430 189 47 67 690
500100750600181	7.5	6	3	66.2	PCB-S2OLP/7500KG PHC	9,0 x 27,0	5,0 x 23,7	36.8	430 189 47 67 690
500101000300181	10	3	4	92.8	PCB-S2OLP/10000KG PHC	9,0 x 27,0	5,0 x 23,7	40	360 183 47 65 820
500101000600181	10	6	4	114.4	PCB-S2OLP/10000KG PHC	9,0 x 27,0	5,0 x 23,7	40	360 183 47 65 820

## Technical data

## Blueprint



