

Lever Hoist POWERTEX PLH-S2 with electrogalvanized chain

Product information



The Powertex PLH-S2 Lever Hoist is a high-quality hoist designed for durability, safety, and ease of operation. Its ergonomic ratchet lever and safety-added features ensure smooth and efficient lifting for various industrial applications.

Product benefits:

- **Enhanced safety:** each hoist undergoes dynamic proof load testing at 1.5 times the Working Load Limit (WLL) before leaving the factory, ensuring maximum safety and reliability. The hoist is equipped with a well-covered automatic load reaction brake and features double safety with two brake pawls and four brake springs, exceeding EN 13157 requirements. The load chain is calibrated, proof load tested and meets the requirements of EN 818-7.
- **Smooth and efficient operation:** the compact and lightweight construction, combined with a sprocket wheel equipped with needle bearings and a drive shaft supported by needle and slide bearings, ensures smooth and efficient operation. The fine-calibrated load chain offers quiet and seamless performance.
- **Quality load chain:** the load chain complies with the EN818-7 T(8) standard and features a Chrome 6-free electro-galvanized surface finish to protect it from corrosion.
- **Easy positioning and safe hooks:** swivel hooks at both ends make in-line positioning easy. The hooks are designed to open at overload instead of breaking, enhancing safety. Heavy-duty steel safety latches and deformation check dots forged into the side of the hooks allow for easy overload detection.
- **Convenient maintenance and documentation:** each hoist is RFID-equipped for easy service and inspection, and a QR code provides on-site access to the user manual. [Read more](#)

Material: Durable all steel construction

Marking: According to standard, CE-marked, UKCA-marked, POWERTEX, Model, WLL, Chain, Serial number, User manual/QR code

Temperature range: -10°C up to +50°C

Finish: Powder coated finish and plated frame components

Standard: EN 13157, EN 818-7

Safety factor: 4:1

Lever Hoist POWERTEX PLH-S2 with electrogalvanized chain

Blueprint



Technical data

Part code	WLL ton	Lifting height m	Number of falls	Weight kg	Model	Load chain mm	Hand force max. kg	A mm	B mm	C mm	D, mm	E mm	F mm	H min mm
500500030150880	0.25	1.5	1	2.7	PLH-S2/250KG PHCA	4,0 x 12,0	28.2	100	70	86	163	20	31	235
500500030300880	0.25	3	1	3.23	PLH-S2/250KG PHCA	4,0 x 12,0	28.2	100	70	86	163	20	31	235
500500050150880	0.5	1.5	1	5.2	PLH-S2/500KG PHCA	5,0 x 15,0	24.8	150	90	118	253	22	32	310
500500050300880	0.5	3	1	5.95	PLH-S2/500KG PHCA	5,0 x 15,0	24.8	150	90	118	253	22	32	310
500500050600880	0.5	6	1	7.45	PLH-S2/500KG PHCA	5,0 x 15,0	24.8	150	90	118	253	22	32	310
500500080150880	0.8	1.5	1	6.6	PLH-S2/800KG PHCA	5,6 x 17,0	26.5	158	98	132	273	26	36	340
500500080300880	0.8	3	1	7.6	PLH-S2/800KG PHCA	5,6 x 17,0	26.5	158	98	132	273	26	36	340
500500080400880	0.8	4	1	8.23	PLH-S2/800KG PHCA	5,6 x 17,0	26.5	158	98	132	273	26	36	340
500500080700880	0.8	7	1	10.18	PLH-S2/800KG PHCA	5,6 x 17,0	26.5	158	98	132	273	26	36	340
500500160150880	1.6	1.5	1	11	PLH-S2/1600KG PHCA	7,1 x 21,0	29.5	185	111	145	378	29	43	400
500500160300880	1.6	3	1	12.6	PLH-S2/1600KG PHCA	7,1 x 21,0	29.5	185	111	145	378	29	43	400
500500160400880	1.6	4	1	13.63	PLH-S2/1600KG PHCA	7,1 x 21,0	29.5	185	111	145	378	29	43	400
500500160600880	1.6	6	1	15.73	PLH-S2/1600KG PHCA	7,1 x 21,0	29.5	185	111	145	378	29	43	400
500500320150880	3.2	1.5	1	19.9	PLH-S2/3200KG PHCA	10,0 x 28,0	33.5	212	124	198	418	37	50	520
500500320600880	3.2	6	1	21.8	PLH-S2/3200KG PHCA	10,0 x 28,0	33.5	212	124	198	418	37	50	520
500500320300880	3.2	3	1	23.2	PLH-S2/3200KG PHCA	10,0 x 28,0	33.5	212	124	198	418	37	50	520
500500630150880	6.3	1.5	2	24.6	PLH-S2/6300KG PHCA	10,0 x 28,0	37	212	124	230	418	43	53	640

Lever Hoist POWERTEX PLH-S2 with electrogalvanized chain

Technical data

Part code	WLL ton	Lifting height m	Number of falls	Weight kg	Model	Load chain mm	Hand force max. kg	A mm	B mm	C mm	D, mm	E mm	F mm	H min mm
500500630300880	6.3	3	2	31.2	PLH-S2/6300KG PHCA	10,0 x 28,0	37	212	124	230	418	43	53	640
500500630450880	6.3	4.5	2	31.2	PLH-S2/6300KG PHCA	10,0 x 28,0	37	212	124	230	418	43	53	640
500500631200880	6.3	12	2	47.7	PLH-S2/6300KG PHCA	10,0 x 28,0	37	212	124	230	418	43	53	640
500500900150880	9	1.5	3	50	PLH-S2/9000KG PHCA	10,0 x 28,0	42	212	124	338	418	44	67	730
500500900300880	9	3	3	60	PLH-S2/9000KG PHCA	10,0 x 28,0	42	212	124	338	418	44	67	730