# Chain Sling Powertex 1-leg with Latch Hook, Grade 10

**Product information**



The Chain Sling Powertex 1-leg with latch hook is a single-leg lifting assembly for general industrial use. It is designed for controlled vertical lifting where fast connection, optional shortening, and predictable performance are required.

The standard assembly includes a master link, a Grade 10 chain, a shortening grab hook, a latch hook, and a marking plate with WLL information. This provides a complete and ready-to-use configuration for everyday lifting tasks.

The sling can also be supplied in alternative configurations with different hooks, master links, or shortening options on request.

**Best used for:**

- Straight vertical lifts with a single lifting point
- Repetitive lifting where quick hook engagement improves efficiency

**Product benefits**

- Latch hook enables fast and secure attachment, reducing connection time during repetitive lifting operations
- Integrated grab hook allows chain shortening, supporting accurate load positioning without extra components
- Grade 10 chain provides higher capacity compared to Grade 8, enabling compact setups without increasing chain diameter
- Components crack detection tested, and samples are proof load tested.
- Fatigue rated to 20,000 cycles at 1.5x WLL, helping maintain predictable behaviour in repetitive lifting applications
- Marking plate shows WLL and angle capacities, simplifying load planning and reducing interpretation errors on site

**Configuration notes**

... *Read more*

**Material:** Alloy steel
**Marking:** According to standard, CE-mark
**Temperature range:** -40°C up to +200°C without reduction in WLL
**Finish:** Red powder paint
**Standard:** EN 818-4, AS 3776
*(+25 % WLL)*

**Safety factor:** 4:1
**Grade:** 10

© November 2026 - All Rights Reserved

# Chain Sling Powertex 1-leg with Latch Hook, Grade 10

## Technical data

| Part code | WLL ton |
|---|---|
| 240500600100260 | 1.4 |
| 240500600200260 | 1.4 |
| 240500600300260 | 1.4 |
| 240500600400260 | 1.4 |
| 240500600500260 | 1.4 |
| 240500600600260 | 1.4 |
| 240500600700260 | 1.4 |
| 240500600800260 | 1.4 |
| 240500800100260 | 2.5 |
| 240500800200260 | 2.5 |
| 240500800300260 | 2.5 |
| 240500800400260 | 2.5 |
| 240500800500260 | 2.5 |
| 240500800600260 | 2.5 |
| 240500800700260 | 2.5 |
| 240500800800260 | 2.5 |
| 240501000100260 | 4 |
| 240501000200260 | 4 |
| 240501000300260 | 4 |
| 240501000400260 | 4 |
| 240501000700260 | 4 |
| 240501000500260 | 4 |
| 240501000600260 | 4 |
| 240501000800260 | 4 |
| 240501300100260 | 6.7 |
| 240501300200260 | 6.7 |
| 240501300300260 | 6.7 |
| 240501300400260 | 6.7 |
| 240501300500260 | 6.7 |
| 240501300600260 | 6.7 |
| 240501300700260 | 6.7 |

© November 2026 - All Rights Reserved

POWERTEX | ROPETEX

# Chain Sling Powertex 1-leg with Latch Hook, Grade 10

## Technical data

| Part code | WLL ton |
|---|---|
| 240501300800260 | 6.7 |
| 240501600100260 | 10 |
| 240501600200260 | 10 |
| 240501600300260 | 10 |
| 240501600400260 | 10 |
| 240501600500260 | 10 |
| 240501600600260 | 10 |
| 240501600700260 | 10 |
| 240501600800260 | 10 |
| 240502000200260 | 16 |
| 240502000300260 | 16 |
| 240502000400260 | 16 |
| 240502000500260 | 16 |
| 240502000600260 | 16 |
| 240502000700260 | 16 |
| 240502000800260 | 16 |
| 240502200200260 | 19 |
| 240502200300260 | 19 |
| 240502200400260 | 19 |
| 240502200500260 | 19 |
| 240502200600260 | 19 |
| 240502200700260 | 19 |
| 240502200800260 | 19 |
| 240502600200260 | 26.5 |
| 240502600300260 | 26.5 |
| 240502600400260 | 26.5 |
| 240502600500260 | 26.5 |
| 240502600600260 | 26.5 |
| 240502600700260 | 26.5 |
| 240502600800260 | 26.5 |
| 240503200200260 | 40 |

© November 2026 - All Rights Reserved

# Chain Sling Powertex 1-leg with Latch Hook, Grade 10

## Technical data

| Part code | WLL ton |
|---|---|
| 240503200300260 | 40 |
| 240503200400260 | 40 |
| 240503200500260 | 40 |
| 240503200600260 | 40 |
| 240503200700260 | 40 |
| 240503200800260 | 40 |

© November 2026 - All Rights Reserved