

Chain Sling Powertex 1-leg with Masterlink MC1 and Safety Hook, Grade 10

Product information



The Chain Sling Powertex 1-leg MC-1 with safety hook is a single-leg lifting assembly for general industrial use. It features an MC-1 master link with an integrated shortening function, reducing the number of components and creating a more compact, organised lifting setup.

It is designed for controlled vertical lifting where secure attachment, quick length adjustment, and predictable performance are required.

The assembly includes the MC-1 master link, a Grade 10 chain, a safety hook, and a marking plate with WLL information, providing a complete and ready-to-use configuration.

When to choose this product

Best for:

- Straight vertical lifts with a single lifting point
- Applications where a compact setup with integrated shortening is preferred
- Lifting applications where secure hook closure is required to reduce the risk of unintentional release

Product Benefits

- MC-1 master link with integrated shortener reduces the number of separate components, simplifying setup and handling
- Integrated shortening function allows quick length adjustment without additional hooks or connectors
- Compact assembly supports easier handling and a clearer overview during inspection
- Safety hook provides secure closure, helping reduce the chance of unintentional hook release during lifting
- Grade 10 chain provides higher capacity compared to Grade 8 ones ... [Read more](#)

Material: Alloy steel

Marking: According to standard, CE-marked

Temperature range: -40°C up to +200°C without reduction in WLL

Finish: Red powder paint

Standard: EN 818-4

(+25 % WLL)

Safety factor: 4:1

Grade: 10

Chain Sling Powertex 1-leg with Masterlink MC1 and Safety Hook, Grade 10

Technical data

Part code	Chain diameter mm	WLL ton	EWL m
240500600100300	6	1.4	1
240500600200300	6	1.4	2
240500600300300	6	1.4	3
240500600400300	6	1.4	4
240500600500300	6	1.4	5
240500600600300	6	1.4	6
240500600700300	6	1.4	7
240500600800300	6	1.4	8
240500800100300	8	2.5	1
240500800200300	8	2.5	2
240500800300300	8	2.5	3
240500800400300	8	2.5	4
240500800500300	8	2.5	5
240500800600300	8	2.5	6
240500800700300	8	2.5	7
240500800800300	8	2.5	8
240501000100300	10	4	1
240501000200300	10	4	2
240501000300300	10	4	3
240501000400300	10	4	4
240501000500300	10	4	5
240501000600300	10	4	6
240501000700300	10	4	7
240501000800300	10	4	8
240501300100300	13	6.7	1
240501300200300	13	6.7	2
240501300300300	13	6.7	3
240501300400300	13	6.7	4
240501300500300	13	6.7	5
240501300600300	13	6.7	6

Chain Sling Powertex 1-leg with Masterlink MC1 and Safety Hook, Grade 10

Technical data

Part code	Chain diameter mm	WLL ton	EWL m
240501300700300	13	6.7	7
240501300800300	13	6.7	8
240501600100300	16	10	1
240501600200300	16	10	2
240501600300300	16	10	3
240501600400300	16	10	4
240501600500300	16	10	5
240501600600300	16	10	6
240501600700300	16	10	7
240501600800300	16	10	8