Chain Sling Powertex 2-leg with Masterlink MC2 and Latch Hooks, Grade 10

Product information



The Chain Sling Powertex 2-leg MC-2 with latch hooks is a two-leg lifting assembly for general industrial use. It features an MC-2 master link with an integrated shortening function, reducing the number of components and creating a more compact and manageable lifting setup.

It is designed for controlled lifting where fast connection, quick length adjustment, and predictable performance are required.

The assembly includes the MC-2 master link, Grade 10 chain, latch hooks, and a marking plate with WLL information, providing a complete, ready-to-use configuration.

Best used for:

- Balanced lifting using two lifting points
- Applications where a compact setup with integrated shortening is preferred
- Repetitive lifting where fast and efficient hook connection improves handling speed

Product benefits

- MC-2 master link integrates shortening functions on both legs, reducing the number of components and simplifying assembly configuration
- Individual leg shortening allows quick length adjustment without adding separate shortening hooks
- Compact design supports a clearer overview during use and inspection, helping reduce handling errors
- Latch hook enables fast and secure attachment, reducing connection time during repetitive lifting operations
- Grade 10 chain provides higher capacity compared to Grade 8, enabling compact setups without increasing chain diameter

... *Read more*

Material: Alloy steel
Marking: According to standard, CE-mark
Temperature range: -40°C up to +200°C without reduction in WLL
Finish: Red powder paint
Standard: EN 818-4, AS 3776
(+25 % WLL)

Safety factor: 4:1
Grade: 10

© November 2026 - All Rights Reserved

POWERTEX | ROPETEX

Chain Sling Powertex 2-leg with Masterlink MC2 and Latch Hooks, Grade 10

Technical data

Part code	Chain diameter mm	WLL ton	EWL m	WLL 0-45° t	WLL 45-60° t	Weight kg
240800600100230	6	2	1	2	1.4	2.84
240800600200230	6	2	2	2	1.4	4.44
240800600300230	6	2	3	2	1.4	6
240800600400230	6	2	4	2	1.4	7.6
240800600500230	6	2	5	2	1.4	9.2
240800600600230	6	2	6	2	1.4	10.8
240800600700230	6	2	7	2	1.4	12.4
240800600800230	6	2	8	2	1.4	14
240800800100230	8	3.55	1	3.55	2.5	5.3
240800800200230	8	3.55	2	3.55	2.5	8.3
240800800300230	8	3.55	3	3.55	2.5	11.3
240800800400230	8	3.55	4	3.55	2.5	14.3
240800800500230	8	3.55	5	3.55	2.5	17.3
240800800600230	8	3.55	6	3.55	2.5	20.3
240800800700230	8	3.55	7	3.55	2.5	23.3
240800800800230	8	3.55	8	3.55	2.5	26.3
240801000100230	10	5.6	1	5.6	4	9.4
240801000200230	10	5.6	2	5.6	4	14
240801000300230	10	5.6	3	5.6	4	18.6
240801000400230	10	5.6	4	5.6	4	23.2
240801000500230	10	5.6	5	5.6	4	27.8
240801000600230	10	5.6	6	5.6	4	32.4
240801000700230	10	5.6	7	5.6	4	37
240801000800230	10	5.6	8	5.6	4	41.6
240801300100230	13	9.5	1	9.5	6.7	15.7
240801300200230	13	9.5	2	9.5	6.7	23.5
240801300300230	13	9.5	3	9.5	6.7	31.3
240801300400230	13	9.5	4	9.5	6.7	39.1
240801300500230	13	9.5	5	9.5	6.7	47
240801300600230	13	9.5	6	9.5	6.7	54.7

© November 2026 - All Rights Reserved

Chain Sling Powertex 2-leg with Masterlink MC2 and Latch Hooks, Grade 10

Technical data

Part code	Chain diameter mm	WLL ton	EWL m	WLL 0-45° t	WLL 45-60° t	Weight kg
240801300700230	13	9.5	7	9.5	6.7	62.5
240801300800230	13	9.5	8	9.5	6.7	70.3
240801600200230	16	14	2	14	10	36.3
240801600300230	16	14	3	14	10	47.9
240801600400230	16	14	4	14	10	59.5
240801600500230	16	14	5	14	10	71.1
240801600600230	16	14	6	14	10	82.7
240801600700230	16	14	7	14	10	94.3
240801600800230	16	14	8	14	10	105.9

© November 2026 - All Rights Reserved