

## Chain Sling Powertex 2-leg with Masterlink MC2 and Latch Hooks, Grade 10

### Product information



The Chain Sling Powertex 2-leg MC-2 with latch hooks is a two-leg lifting assembly for general industrial use. It features an MC-2 master link with an integrated shortening function, reducing the number of components and creating a more compact and manageable lifting setup.

It is designed for controlled lifting where fast connection, quick length adjustment, and predictable performance are required.

The assembly includes the MC-2 master link, Grade 10 chain, latch hooks, and a marking plate with WLL information, providing a complete, ready-to-use configuration.

#### When to choose this product:

##### Best for:

- Balanced lifting using two lifting points
- Applications where a compact setup with integrated shortening is preferred
- Repetitive lifting where fast and efficient hook connection improves handling speed

#### Product benefits

- MC-2 master link integrates shortening functions on both legs, reducing the number of components and simplifying assembly configuration
- Individual leg shortening allows quick length adjustment without adding separate shortening hooks
- Compact design supports a clearer overview during use and inspection, helping reduce handling errors
- Latch hook enables fast and secure attachment, reducing connection time during repetitive lifting operations
- Grade 10 chain provides higher capacity compared to Grade 8 chains ... [Read more](#)

**Material:** Alloy steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40°C up to +200°C without reduction in WLL

**Finish:** Red powder paint

**Standard:** EN 818-4

(+25 % WLL)

**Safety factor:** 4:1

**Grade:** 10

## Chain Sling Powertex 2-leg with Masterlink MC2 and Latch Hooks, Grade 10

### Technical data

Part code	Chain diameter mm	WLL ton	EWL m	WLL 0-45° t	WLL 45-60° t
240800600100230	6	2	1	2	1.4
240800600200230	6	2	2	2	1.4
240800600300230	6	2	3	2	1.4
240800600400230	6	2	4	2	1.4
240800600500230	6	2	5	2	1.4
240800600600230	6	2	6	2	1.4
240800600700230	6	2	7	2	1.4
240800600800230	6	2	8	2	1.4
240800800100230	8	3.55	1	3.55	2.5
240800800200230	8	3.55	2	3.55	2.5
240800800300230	8	3.55	3	3.55	2.5
240800800400230	8	3.55	4	3.55	2.5
240800800500230	8	3.55	5	3.55	2.5
240800800600230	8	3.55	6	3.55	2.5
240800800700230	8	3.55	7	3.55	2.5
240800800800230	8	3.55	8	3.55	2.5
240801000100230	10	5.6	1	5.6	4
240801000200230	10	5.6	2	5.6	4
240801000300230	10	5.6	3	5.6	4
240801000400230	10	5.6	4	5.6	4
240801000500230	10	5.6	5	5.6	4
240801000600230	10	5.6	6	5.6	4
240801000700230	10	5.6	7	5.6	4
240801000800230	10	5.6	8	5.6	4
240801300100230	13	9.5	1	9.5	6.7
240801300200230	13	9.5	2	9.5	6.7
240801300300230	13	9.5	3	9.5	6.7
240801300400230	13	9.5	4	9.5	6.7
240801300500230	13	9.5	5	9.5	6.7
240801300600230	13	9.5	6	9.5	6.7

## Chain Sling Powertex 2-leg with Masterlink MC2 and Latch Hooks, Grade 10

### Technical data

Part code	Chain diameter mm	WLL ton	EWL m	WLL 0-45° t	WLL 45-60° t
240801300700230	13	9.5	7	9.5	6.7
240801300800230	13	9.5	8	9.5	6.7
240801600200230	16	14	2	14	10
240801600300230	16	14	3	14	10
240801600400230	16	14	4	14	10
240801600500230	16	14	5	14	10
240801600600230	16	14	6	14	10
240801600700230	16	14	7	14	10
240801600800230	16	14	8	14	10