

Ropetex Thin Lube 30

Product information



ROPETEX

Ropetex Thin Lube 30 is a semi-dry thin film lubricant that can be utilized in a wide range of applications, both in industry and construction. It has excellent penetration and corrosion resisting properties. Thin Lube 30 also minimizes wear between the wires and strands of a steel wire rope, and is therefore perfect for frequent use in harsh working conditions. It also consists of components that reduce abrasive particle contamination, the probability of lubricant 'flinging off' and a lubricant build-up

Typical applications:

- General industrial lifting
- winch ropes
- tower cranes
- mobile cranes
- dockside cranes
- fishing ropes

Application methods: Portable sprayer or brushing/dripping.

Minimum application temperature: -5°C (product should be kept to at least 10°C for 48 hours before application).

Color/texture: Brown opaque fluid.

NLGI Grade: Solvent liquid

4-ball weld load: > 100 kgf

Available in 400 ml aerosol, 5 liter can and 20 liter can.

... [Read more](#)

Temperature range: -30°C up to +60°C

Ropetex Thin Lube 30

Technical data

| Part code | Description |
|--------------|--------------------------------------|
| 142500040010 | Ropetex Thin Lube 30, 400 ml aerosol |
| 142500500010 | Ropetex Thin Lube 30, 5 lit can |
| 142502000010 | Ropetex Thin Lube 30, 20 lit drum |