

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier Product name:

ROPETEX THIN LUBE 30

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Anticorrosion product Uses advised against: No uses advised against identified.

1.3 Details of the supplier of the safety data sheet

Manufacturer / Supplier Telephone:	SCM CITRA OY Asessorinkatu 3-7 20780 Kaarina Finland +358 2 5115511		
Contact Person: E-mail:	SCM Citra Product Director edc.sales@scmcitra.com		
1.4 Emergency telephone number:	UK NHS: Dial 111		

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

The product has been classified and labelled as hazardous according to regulation GB-CLP.

Classification according to GB-CLP.

Physical Hazards		
Flammable liquids	Category 3	H226: Flammable liquid and vapor.
Health Hazards		
Specific Target Organ Toxici Single Exposure	ty - Category 3	H336: May cause drowsiness or dizziness.
Specific Target Organ Toxici Repeated Exposure	ty - Category 1	H372: Causes damage to organs through pro- longed or repeated exposure.
Aspiration Hazard	Category 1	H304: May be fatal if swallowed and enters air- ways.
Environmental Hazards		
Chronic hazards to the aquater environment	tic Category 2	H411: Toxic to aquatic life with long lasting ef- fects.
Hazard summary Physical Hazards:	Can form flammable va	pour-air mixtures during the application.



Health Hazards Inhalation:	Has a narcotic effect.
Skin Contact:	At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.
Ingestion:	If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.
2.2 Label Elements Contains:	White Spirit, low viscous
Signal Words:	Danger
Hazard Statement(s):	 H226: Flammable liquid and vapor. H336: May cause drowsiness or dizziness. H372: Causes damage to organs through prolonged or repeated exposure. H304: May be fatal if swallowed and enters airways. H411: Toxic to aquatic life with long lasting effects.
Precautionary Statemen	ts
Prevention:	P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260: Do not breathe dust/fume/gas/mist/vapors/spray. P273: Avoid release to the environment.
Response:	P301+P310: IF SWALLOWED: Immediately call a POISON CEN- TER/doctor. P331: Do NOT induce vomiting.
Disposal:	P501: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Supplemental label info	r mation EUH066: Repeated exposure may cause skin dryness or cracking.
2.3 Other hazards:	By handling of mineral oil products and chemical products no particular hazard is known when normal precautions (item 7) and personal protective equipment (item 8) are kept. The product may not be released into the environment without control.

SECTION 3: Composition/information on ingredients

3.2 Mixtures



General information:

Mixture based on severely refined mineral base oils and corrosion preventive agents in volatile hydrocarbons with a flashpoint below 55°C.

Chemical name	Identifier		UK-REACH Regis- tration No.	Notes
White Spirit, low viscous	EC: 919-446-0	50,00% - <100,00%		
diacetone alcohol	EINECS: 204-626-7	0,10% - <1,00%		

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

Classification

Chemical name	Identifier	Classification	
White Spirit, low viscous	EC: 919-446-0	GBCLP: Asp. Tox. 1;H304, Flam. Liq. 3;H226, STOT SE 3;H336, Aquatic Chronic 2;H411, STOT RE 1;H372	
diacetone alcohol	EINECS: 204-626-7	GBCLP: STOT SE 3;H335, Eye Irrit. 2;H319, Repr. 2;H361d	

GB-CLP

specific concentration limit

Chemical name		specific concentra- tion limit		Category	Hazard state- ments
diacetone alcohol	EINECS: 204-626-7	>= 10 %	Serious eye irritation	2	H319

For the wording of the listed hazard statements refer to section 16.

Please note that the mineral oils and petroleum distillates used in our products are severely refined and have a DMSO extract < 3% as measured by method IP 346 and are not classified as carcinogenic according to Nota L/ Nota N of Annex VI of Regulation GB-CLP.

SECTION 4: First aid measures

General:	Instantly remove any clothing soiled by the product.
4.1 Description of first aid measu Inhalation:	ures Supply fresh air; consult doctor in case of symptoms.
Eye contact:	Promptly wash eyes with plenty of water while lifting the eye lids.
Skin Contact:	Get medical attention if symptoms occur. Take off immediately all contami- nated clothing. Rinse skin with water [or shower]. Wash with water and soap; pay attention: skin degreasing product.
Ingestion:	Call a physician or poison control center immediately. Rinse mouth. Never give liquid to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do NOT induce vomiting.
4.2 Most important symptoms and effects, both acute and delayed:	If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately. Headache.
Issue Date: 05.08.2015	



Froduct name: ROPETEX THIN LO				
4.3 Indication of any immediate medical attention and spe- cial treatment needed	Get medical attention if symptoms occur.			
SECTION 5: Firefighting measures	5			
General Fire Hazards:	Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.			
5.1 Extinguishing media				
Suitable extinguishing me- dia:	CO2, fire extinguishing powder or fog like water spraying. Extinguish larger fires with alcohol resistant foam or spray water with suitable surfactant added			
Unsuitable extinguishing media:	Avoid water in straight hose stream; will scatter and spread fire.			
5.2 Special hazards arising from the substance or mix- ture:	Can form explosive vapor-air mixtures at higher temperatures.			
5.3 Advice for firefighters				
Special fire-fighting proce- dures:	Move container from fire area if it can be done without risk. Dispose of fire debris and contaminated fire fighting water inaccordance with official regulations. Collect contaminated fire fighting water separately. It must not enter drains.			
Special protective equip- ment for fire-fighters:	Firefighters must use standard protective equipment including flame retard- ant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Self-contained breathing apparatus and full protective cloth- ing must be worn in case of fire.			

SECTION 6: Accidental release measures

6.1 Personal precautions, pro- tective equipment and emergency procedures:	Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. In case of spills, beware of slippery floors and surfaces. Keep away from sources of ignition - No smoking.
6.2 Environmental Precautions:	Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water sources or sewer. Prevent from spread- ing (e.g. by binding or oil barriers). Environmental manager must be in- formed of all major spillages. Do not allow to enter drainage system, sur- face or ground water.
6.3 Methods and material for containment and cleaning up:	Absorb with liquid-binding material (sand, diatomite, acidbinders, universal binders, sawdust). Dispose of the material collected according to regulations. Stop the flow of material, if this is without risk.
6.4 Reference to other sec- tions:	See Section 8 of the SDS for Personal Protective Equipment. See Section 7 for information on safe handling See Section 13 for information on disposal.



Dike for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of material, if this is without risk.

SECTION 7: Handling and storage:

7.1 Precautions for safe han- dling:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Use only in well- ventilated areas. Risk of vapor concentration on the floor and in low-lying areas. Prevent formation of aerosols. Do not eat, drink or smoke when working with the product. Take usual precautions when handling mineral oil products or chemical products. Observe good industrial hygiene practices. Provide adequate ventilation.
7.2 Conditions for safe storage, including any incompatibili- ties:	Store locked up. Store in a well-ventilated place. Store in a cool place. Lo- cal regulations concerning handling and storage of waterpolluting products have to be followed. The precautions for storing and handling of flammable liquids have to be kept. Local regulations for common storage of flammable liquids have to be followed. Do not heat up to temperatures close to the flash point.
7.3 Specific end use(s):	Not applicable
Storage Class:	3, Flammable Liquids

SECTION 8: Exposure controls/personal protection

8.1 Control Parameters

Occupational Exposure Limits

Chemical name	Туре	Exposure Limit Values		Source
diacetone alcohol	TWA	50 ppm	241 mg/m3	UK. EH40 Workplace Exposure Limits (WELs), as amended (12 2011)
diacetone alcohol	STEL	75 ppm	362 mg/m3	UK. EH40 Workplace Exposure Limits (WELs), as amended (12 2011)

8.2 Exposure controls

controls:

Appropriate engineering Provide adequate ventilation. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

General information: Wash hands before breaks and after work. Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. The usual precautionary measures should be adhered to inhandling the chemicals or the mineral oil products.



Eye/face protection:	Safety glasses (EN 166) recommended during refilling. Avoid contact with skin and eyes. Goggles/face shield are recommended. If risk of splashing, wear safety goggles or face shield.
Skin protection Hand Protection:	Material: Nitrile butyl rubber (NBR). Min. Breakthrough time: >= 480 min Recommended thickness of the material: >= 0,38 mm Avoid long-term and repeated skin contact. Suitable gloves can be recom- mended by the glove supplier. Use skin protection cream for preventive skin protection. Protective gloves, where permitted in acc. to safety direc- tions. The exact break through time has to be found out by the manufactur- er of the protective gloves and has to be observed.
Other:	Do not carry cleaning cloths impregnated with the product in trouser pock- ets. Wear suitable protective clothing.
Respiratory Protection:	Ensure good ventilation/exhaustion at the workplace. Avoid breathing vapour/ aerosol.
Thermal hazards:	Not known.
Hygiene measures:	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated foot- wear that cannot be cleaned.
Environmental Controls:	No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	
Physical state:	liquid
Form:	liquid
Color:	Brown
Odor:	Characteristic
pH:	substance/mixture is non-soluble (in water)
Freezing point:	not determined
Boiling Point:	not determined
Flash Point:	40 °C
Evaporation Rate:	Not applicable for mixtures
Flammability (solid, gas):	not determined
Flammability Limit - Upper (%):	Not applicable for mixtures
Flammability Limit - Lower (%):	Not applicable for mixtures
Vapor pressure:	Not applicable for mixtures
Relative vapor density:	Not applicable for mixtures
Density:	0,82 g/cm3 (15 °C)
Solubility(ies)	
Solubility in Water:	Insoluble in water



Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	Not applicable for mixtures
Auto-ignition temperature:	not determined
Decomposition Temperature:	not determined
Kinematic viscosity:	< 20,5 mm2/s (40 °C)
Explosive properties:	Value not relevant for classification
Oxidizing properties:	Value not relevant for classification
Particle characteristics:	Not applicable
9.2 Other information	No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity:	Stable under normal use conditions.
10.2 Chemical Stability:	Material is stable under normal conditions.
10.3 Possibility of hazardous reactions:	Stable under normal use conditions.
10.4 Conditions to avoid:	Heat, sparks, flames.
10.5 Incompatible Materials:	Strong oxidizing substances. Strong acids. Strong bases.
10.6 Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and oth- er toxic gases or vapors.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Oral Product: Specified substance(s)	Not classified for acute toxicity based on available data.
White Spirit, low viscous	LD 50 (Rat): > 15.000 mg/kg
diacetone alcohol	LD 50 (Rat): 3.020 mg/kg (OECD 401)
Dermal Product: Specified substance(s) diacetone alcohol	Not classified for acute toxicity based on available data. LD 50 (Rabbit): 13.750 mg/kg
Inhalation Product: Specified substance(s) White Spirit, low viscous	Not classified for acute toxicity based on available data. LC 50 (Rat, 4 h): > 13,1 mg/l



Skin Corrosion/Irritation: Product: Specified substance(s) diacetone alcohol	Based on available data, the classification criteria are not met. OECD 404 (Rabbit, 24 h): Not irritant.
Serious Eye Damage/Eye In Product: Specified substance(s) diacetone alcohol	itation: Based on available data, the classification criteria are not met. OECD 405 (Rabbit): Irritating to eyes.
Respiratory or Skin Sensitiz Product:	Exation: Skin sensitizer: Based on available data, the classification criteria are not met. Respiratory sensitizer: Based on available data, the classification criteria are not met.
Specified substance(s) diacetone alcohol	(Guinea Pig) No sensitizing effect (guinea pig); OECD 406
Germ Cell Mutagenicity Product:	Based on available data, the classification criteria are not met.
Carcinogenicity Product:	Based on available data, the classification criteria are not met.
Reproductive toxicity Product:	Based on available data, the classification criteria are not met.
Specific Target Organ Toxic Product:	ity - Single Exposure Based on available data, the classification criteria are met.
Specific Target Organ Toxicity - Repeated Exposure Product: Based on available data, the classification criteria are met.	
Aspiration Hazard Product:	May be fatal if swallowed and enters airways.
Other adverse effects:	No data available.

SECTION 12: Ecological information

12.1 Toxicity

Acute toxicity Product:	Based on available data, the classification criteria are not met.
Fish Specified substance(s) White Spirit, low viscous	LC 50 (Fish, 96 h): 10 - 30 mg/l
diacetone alcohol	LC 50 (Fish, 96 h): > 100 mg/l (OECD 203)



Aquatic Invertebrates Specified substance(s) White Spirit, low viscous	EC 50 (Water Flea, 48 h): 10 - 20 mg/l (OECD 202)
diacetone alcohol	EC 50 (Water Flea, 48 h): > 1.000 mg/l (OECD 202)
Chronic Toxicity Product:	Based on available data, the classification criteria are met.
Aquatic Invertebrates Specified substance(s) diacetone alcohol	NOEC (Water Flea, 21 d): 100 mg/l (OECD 211)
Toxicity to Aquatic Plants Specified substance(s) White Spirit, low viscous	EC 50 (Alga, 72 h): 4,6 - 10 mg/l (OECD 201)
diacetone alcohol	EC 50 (Alga, 72 h): > 1.000 mg/l (OECD 201)
12.2 Persistence and Degradabili	ty
Biodegradation Product: Specified substance(s) diacetone alcohol	Not applicable for mixtures 98,51 % (28 d, OECD 301A) Readily biodegradable
12.3 Bioaccumulative potential Product:	Not applicable for mixtures
12.4 Mobility in soil: Product:	Not applicable for mixtures
12.5 Results of PBT and vPvB assessment:	The product does not contain any substances fulfilling the PBT/vPvB crite- ria.
12.6 Other adverse effects:	Toxic to aquatic life with long lasting effects.
Water Hazard Class (WGK):	WGK 2: significantly water-endangering.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

General information:	Dispose in accordance with all applicable regulations.
Disposal methods:	Discharge, treatment, or disposal may be subject to national, state, or local laws.

List of Waste (LoW) Codes

12 01 99: wastes not otherwise specified



SECTION 14: Transport information

ADR/RID

UN 1993 FLAMMABLE LIQUID, N.O.S.(White Spirit, low viscous, diacetone alcohol)
3 3 30 (D/E) III Dangerous for the environment –
UN 1993 FLAMMABLE LIQUID, N.O.S.(White Spirit, low viscous, diacetone alcohol)
3 3 F-E, S-E
III Marine pollutant –
UN 1993 Flammable liquid, n.o.s.(White Spirit, low viscous, diacetone alco- hol)
3 3
III Dangerous for the environment –

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code: Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

GB Regulations

The Ozone-Depleting Substances and Fluorinated Greenhouse Gases (Amendment etc.) (EU Exit) Regulations 2019: none

The Persistent Organic Pollutants (Amendment) (EU Exit) Regulations 2020: none



Product name: ROPETEX THIN LUBE 30	
National Regulation	ons
Water Hazard Clas (WGK):	ss WGK 2: significantly water-endangering.
15.2 Chemical safety a sessment:	Is- No Chemical Safety Assessment has been carried out.
SECTION 16: Other info	ormation
Revision Information:	Vertical lines in the margin indicate an amendment.
Wording of the H-state	ements in section 2 and 3
H226	Flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
Other information:	The classification complies with the current GB lists; however, it has been supplemented with expert literature information and information provided by/about our company. The following evaluation methods were used: On the basis of test data; Calculation Method; Bridging Principle "Substantially simi- lar mixtures"; Expert Judgement
Revision Date: Disclaimer:	12.09.2023 The data contained in this safety data sheet are based on our current knowledge and experience and are given to the best of our knowledge and belief. It characterizes the product only with regard to safety requirements for handling, transport and disposal. The data do not describe the product's properties (tech. product specification). Neither should any agreed property nor the suitability of the product for any specific technical application be de- duced from the data contained in this safety data sheet. Modifications on this document are not allowed. The data are not transferable to other products. In the case of mixing the product with other products or in the case of pro- cessing, the data in this safety data sheet are not necessarily valid for the new-made material. It is the responsibility of the recipient of the product to observe federal, state and local law. Please contact us to obtain up-to-date safety data sheets. This document was issued electronically and has no sig- nature.